

MORSEL™

675

Morsel 675 Superior Gasketing Compound



Superior Gasketing

Compound

TRUST	Ease of Applications
MORSEL	Wide Versality
FOR	Out Standing Physical Properties

Quality engineered to replace 100% of conventional precut gaskets.

A press of a finger & different shapes & thickness gaskets are formed

Highly Flexible ,even after heat agening.

Special Features

Oil Tolerant

Excellent thermal resistant of cured product.
 Excellent chemical resistance of cured product
 Supports direct metal-to-metal /metal to other flange design
 is self-adhering and leak-proof

Out Standing Properties

Can tolerate micromovements on highly stressed flanges
 Immediate in-line sealing tests possible
 Cures through limited oil films
 Ideal for engine compartment applications
 Suitable for use with oils and coolants
 Eliminates the need for shimmed flanges

Easy-to-Service

Ideal for frequently serviced flanges.
 Fully cured product easily removed from flange.
 Can be removed without harsh solvents

Less damage to flange, shorter repair times
 Eliminates cost and hazards associated
 with harsh solvents
 Eliminates damage to flange
 Immediate in-line sealing tests possible

Can be removed without scrapping or sanding
 Instant low pressure seal

USE FOR

Morsel 675 replaces virtually every type of cork, felt, rubber.
 All Types of Flanges • Cover Plates • Hose Connections .
 Thread Assemblies.Oil Pans 7 Pumps. Water Pump & Housing.

Product Data

Application	Cure Stare	Temp.Range	Gap Fill	Viscosity
Gasketing Cum Thread Locker	Flexible	-55 to 500 °C	2 mm	Thixotropic

Packing 250 MI

Morsel 675

Morsel Enggtech Pvt. Ltd

Ganeshan Complex,
 146,Gumanpura Kotri Road,
 KOTA Rajasthan 324007 INDIA
 Phone :91 -744 -2390292,2391392,2392492 Fax 2391392
 Email: morsel@rediffmail.com
 info@morsel.co.in
 www.morsel.co.in